FLOW-iD® 25000

Model Name	Flow-iD™
Model Number	25000
Submodels	Primary (25001) & Remote (24001)
Primary Device	
Model Number	25001
Radio Frequency	2.4 GHz
Ports	24 VAC IN, 24 VAC OUT, Sensor (2), Antenna (1)
# Antennas	1 detachable external adjustable antenna
LEDs	Pair, Fault, Remote Sensor, Backup Sensor, Primary Sensor, 24 VAC IN, 24 VAC OUT
Button	Pair
Switch	On/Off
Sensor	10 -12 VDC
Primary Device Environmental	
Dimensions	6” x 5.3” x 4.9” / 152.4 x 134.6 x 124.5 mm
Unit Weight	.82kg /1.8 lbs
Power (max)	24 VAC (80VA)
Power (min)	24 VAC (48VA)
Certification	
Operating Temperature	-25 … 70°C / -13 … 158°F
Storage Temperature	-40 … 85 °C / -40 … 185 °F
Remote Device	
Model Number	24001
Radio Frequency	2.4 GHz
Ports	Sensor (1)
# Antennas	Internal
LEDs	Pair
Button	Pair
Sensor	10-12 VDC
Remote Device Environmental	
Dimensions	6” x 5.3” x 4.9” / 152.4 x 134.6 x 124.5 mm
Unit Weight	.82 kg / 1.8 lbs
Power (nominal)	6 VDC (4 X AA) Lithium or Alkaline
Certification	
Operating Temperature	-17 … 55°C / 0 … 131°F
Storage Temperature	-40 … 85°C / -40 … 185 °F